

Simple handheld dew point meter AH-192DS

Product Description

Widely used in workshops, offices, plantes, libraries, computer stations, laboratories and warehouses.



Product Features

- * The Last Values / Max. Values / Min. Values of both Humidity and Temperature will be automatically stored in memory and can be displayed by turn.
- * The use of durable, long-lasting components, including a strong, light weight ABS-plastic housing assures maintenance free performance for many years. The housing has been carefully shaped to fit in either hand.
- * Used the exclusive MICRO-COMPUTER LSI circuit and crystal time base to offer the high accuracy measurement & fast measuring time.
- * Digital display gives exact reading with no guessing.
- * Wide measuring range & high resolution.

Product Parameter

Parameters Measured	Dew Point Temperature, Wet Bulb Temperature, Temperature, Humidity	
Measuring Range	Dew Point: -20°C~40°C	Temp.: -10~60 °C (14~140 F)
	Wet Bulb Temp.: -10°C~60°C (14°F~140°F)	Humidity: 10~95 %RH
Resolution	Dew Point: 0.1°C	Temp. resolution: 0.1°C / 0.1°F
	Wet Bulb Temp.: 0.1°C / 0.1°F	Humidity: 0.1%R.H
Accuracy	Dew Point: ±1°C	Temp.: ±0.5°C
	Wet Bulb Temp.: ±0.5°C	Humidity: 2.5 %±1%R.H
Sensor Type	Humidity: Capacitor	Temp. Resistor
Sampling Time	0.4 Seconds	
Memory	Last Value, Max. Value, Min Value	
Operating Conditions	Temperature : 0~50°C	Humidity: below 90% RH
Power Supply	4X1.5v AAA (UM-4 Battery)	
Size	140x71x31 mm	
Weight	145 g / 0.32 lb (Not Including Batteries)	

Product Accessories

Standard Accessories	Main Unit
	Carrying Case
	Operation Manual
Operation Accessories	USB data output
	Bluetooth data output